## **GIGAMED!**A



# 1080P AHD IR HIGH SPEED DOME CAMERA 100 M IR DISTANCE GGM CCH2SD20XIR



1/2.8" CMOS sensor

Optical zoom x20

IP66

**AHD 1080P** 

Privacy mask

The new GIGAMEDIA AHD speed dome is a strong and powerful solution for your videosurveillance projects.

It embeds 20X optical zoom and IR LED are able to light up to 100 m. The 1080P resolution provides a very good picture quality in all kind of situation in day and night time. This camera is very easy to manage and is compliant with GIGAMEDIA DVR range. The wiper helps you to clean the glass of your speed dome to have the best possible view in all-weather condition.

This speed dome is suitable for many cases such as cities, industrial sites, high security sites ...

#### MAIN

#### **FEATURES**

- 1080P AHD
- 100 m IR distance
- Full aluminum alloy wiper
- OSD menu in english
- 256 preset points
- Video analysis light-adjustment technology
- IP66 all-environments protection
- Optical zoom 20X
- Privacy mask

ed. 23/08/2016 WWW.GIGAMEDIA.NET

# **GIGAMED[A**



### PRODUCT


### **SPECIFICATION**

MODEL	
	GGM CCH2SD20XIR
SENSOR	
Image sensor Resolution	1/2.8" CMOS Sony IMX322 1080P (1920x1080)
LENS	
Zoom	20x optical zoom,
•	10x digital zoom
Iris	Fixed
	$f = 4.9 \sim 97 \text{ mm}$
Mini. illumination	0.05 lx (color)
	0.01 lx (B/W)
IR-cut	Auto/Manual
Shutter time	1/1 ~ 1/10,000 s
VIDEO	

Julice tille	1/1 - 1/10,000 3
VIDEO	
Day/Night	ON / OFF / auto
BLC	ON / OFF
White balance	Auto / Manual / Ggain / Bgain
Noise reduction	2DNR / 3DNR
	PelcoP/D
AGC	Auto / Manual
Privacy mask	4 zones

SPEED DOME SPE	CIFICATION
Pan range	360°
Tilt range	-10°~90°
Manual speed	Horizontal: 0.01 °/s - 350 °/s,
-	Vertical: 0.01 °/s - 120 °/s
Preset speed	Pan : 350°/s - Tilt: 120°/s
Preset	256
Auto cruising	8 groups (32 preset/group)
Auto scan	8 groups
	(setup left and right boundary)
Pattern scanning	4 groups
Wiper	Manual activation
Bracket	Wall mount / Pendant mount
	(optional)
OSD menu	English

POWER SUPPLY	
Power input	DC 12 V ±10% included
Power consump	tion ≤50 W
ENVIRONMENT	
Working temp.	-35 °C to +60 °C
Humidity	<90%, no condensing
PROTECTION	7 c 70, no condensing
ROTEOTION	IP66
	3000 V anti-surge design
DIMENOLON	Juuu v aliti-surye uesiyii
DIMENSION	
	See sketch below
WEIGHT	
	5.8 kg
WARRANTY	
	2 years
	,



ed. 23/08/2016 WWW.GIGAMEDIA.NET