

8-PORT SOHO GIGABIT ETHERNET SWITCH

GGM GS08



Metal Case with Internal Power

Auto-MDI/MDI-X

Auto-Negotiation

Non-Blocking

Store and Forward

Smart Plug and Play

GGM GS08 is 8-port SOHO Gigabit Ethernet Switch that is designed for small or medium network environment to strengthen its network connection. This product is compact in size, making it ideal for SOHO users with limited space. It is a superb choice for expanding your network.

HIGH-SPEED NETWORKING

GGM GS08 provides an excellent solution for expanding your Gigabit network. By Gigabit speed, this product provides high flexibility and high bandwidth connectivity to servers, workstations and other attached devices. It enables you to save time transferring large files.

AUTO-MDI/MDI-X

Every port can automatically sense your type of cable, so there is no need for crossover cables whether you are connecting this switch to another switch or to a computer.

AUTO-NEGOTIATION


Every port can automatically sense if the connected network devices are running at 10Mbps, 100Mbps or 1000Mbps and Half/Full-Duplex mode, and adjust accordingly.

NON-BLOCKING

This switch receives and forwards traffic seamlessly with its non-blocking wire-speed. Every port simultaneously supports up to 2000Mbps of bandwidth in full-duplex mode. This feature provides full wire speed to the connected devices and allows you to run a smooth network.

STORE AND FORWARD

By this function, this switch can maximize network performance while minimizing the propagation of bad network packets.



PRODUCT SPECIFICATION

Standards	IEEE 802.3 10BaseT IEEE 802.3u 100BaseTX IEEE 802.3ab 1000BaseT IEEE 802.3x Flow Control
Features	Number of Ports: 8 MAC Address: 4K Buffer Memory: 128 KB Jumbo Frames: 9 KB Transmission Method: Store and Forward
Filtering/Forwarding Rates	1000Mbps port - 1,488,000pps 100Mbps port - 148,800pps 10Mbps port - 14,880pps
Transmission Media	10BaseT Cat. 3, 4, 5 UTP/STP 100BaseTX Cat. 5 UTP/STP 1000BaseT Cat. 5E UTP/STP
Led Indicators	Per Port: Link/Act, 1000M Per Unit: Power
Power Supply	90~260V/AC, 50~60Hz
Power Consumption	6 Watts (Max)
Dimensions	175 × 80 × 24 mm (L x W x H)
Weight	0.42 kg
Operating Temperature	0 to 55°C
Storage Temperature	-20 to 90°C
Humidity	10 to 90% RH (non-condensing)
Certifications	FCC Class B, CE

PART NUMBER

P/N	DESCRIPTION
GGM GS08	8-port SOHO Gigabit Ethernet Switch

YOUR POINT OF CONTACT