HDMI 2.0 BI-Direction Switch USER Manual	1.0 Introduction 4K HDMI BI-Direction Switch can switch two signal sources like blu-ray player and computer to one display like HDTV.Or switch one signal source like DVD Player between two displays like TV or monitor.so it can't be used as HDMI Splitter. It offers HD solutions for HDTV retail and show site, HDTV, STB, DVD and Projector factory, noise, space and security concerns, data center control, information distribution, conference room presentation, school and corporate training environments.	Peatures & Specification 2 HDMI-Host (DVD Player, PS4 or others) to 1 HDMI Monitor or TV 1 HDMI-Host (DVD Player, PS4 or others) to 2 HDMI Monitor or TV Power free MAX operation current: 15mA Full compliance with the HDMI Specification V1.0,V1.1,V1.3,V1.4,V2.0 Main control: Manual electronic selectic With 2 LED & display working port 3 HDMI A/F connectors LED: 2(Blue, Display working port Easy install & operation Support HDMI Plug & Play Support HDMI Plug & Play Support input up to 5 metres AWG26 HDMI standard cable length, output up to 5 metres AWG26 cable length	3.0 Connection HDMI BI-Direction Switch TV	4 .0 Box Contents Item	The HDMI BI-Direction Switch doesn't appear to be functioning. Firstly, check if the LED lights, if the power supply is in good condition and well connected. Secondly, make sure all cables are in good condition and well connected. Thirdly, make sure the length of the cables is within the maximum supported length of this HDMI BI-Direction Switch. Lastly, please try to connect the input source to the display directly to see if it display normally.
		output up to 5metres AWG26 cable length	1 Host to 2 Device 2 Host to 1 Device		