

Media converter 1000Base-T to 1000BaseSX/LX SFP



Single or Multimode

SFP Port

Auto MDI/MDIX

Standards

IEEE 802.3z
IEEE 802.3ab

Port

RJ45 x 1
SFP x 1

Performance

Bandwidth RJ45: 10/100/1000 Mbps
SFP : 1000 Mbps

SFP Multimode / Singlemode
MTBF 100,000 h


Power supply

Power IN DC5V 1A
Consumption <2W

Physical

Working temperature 0 -60°C
Working humidity 5%~90%
Dimensions 26mm (H) * 71mm (W) * 94 mm (D)

FRONT PANEL



LED SIGNIFICATION

LED	Statut	Description
PWR	ON	Power is ON
	OFF	Power is OFF
100M	ON	100Mbps speed
	OFF	
FX/ACT	ON	Fiber link OK
	Clignotant	Data received or transmitted
	OFF	Fiber link failed
1000M	ON	1000Mbps speed
	OFF	
TP/ACT	ON	Link OK
	Clignotant	Data received or transmitted
	OFF	Link failed
FDX	ON	Full duplex
	OFF	Half duplex

Associated products

GGM MSFPSX	1000Base-SX SFP Module, MMF, LC connector, 550m
GGM MSFPLX	1000Base-LX SFP Module, SMF, LC connector, 10km



TECHNICAL SUPPORT (OUTSIDE FRANCE)

- Technical self-service portal GIGAMEDIA:
<http://support.gigamedia.net>

