

## SmartSwitch48-PortGigabit+4-portSFP +

48 x Gigabit RJ45

4 x SFP+ ports

Smart manageable

Advanced L2 Features



GGM GS200 Web-managed Smart Switches series are designed to fit all the technical requirements of modern converged IP networks. Thanks to their large port versatility and their powerful Layer 2 features, GGM GS200 Smart Switches can deal simultaneously with Multimedia streaming, Multicast flux, security and any other services that could need a large bandwidth amount. GGM GS200 Web-managed Smart Switches offer an affordable Gigabit non-blocking network.

### Advanced Layer 2 Features

With their very much advanced Layer 2 features, the GGM GS200 Smart Switches can perfectly be integrated into modern IP Networks :

- Full network segmentation management with VLAN
- QoS features to optimize each IP flux
- Strong fault tolerance and redundancy with Spanning Tree technologies
- Loopback detection and quarantine of faulty links
- Cable diagnostics for an efficient network

### Strong network security

The GGM GS200 Smart Switches serie comes with the most valuable security technologies to protect your network against intrusion :

- 802.1x RADIUS authentication to ensure a reliable and strong users authentication on the network
- ACL feature to improve the network security and management
- ARP packet inspection to prevent ARP spoofing and networks hacking
- DHCP Snooping feature to prevent the use of rogue DHCP over the network

H/W	
CPU	Microsemi (Vitesse)
DRAM	2G
Flash memory	128M
Port Configuration	
10M/100M/1G RJ45 Port	48
100M/1G SFP Port	0 - (4-Port SFP+ 1G/10G)
Console Port	RJ45
Total Ports	52
HW Performance	
Switching Bandwidth	176Gbps
Forwarding Performance	130.944Mpps
MAC Address	32K
Jumbo Frames	9216 Bytes
Environmental	
Operating Temperature	0°C to 45 °C
Operating Humidity	10 to 90% RH (non-condensing)
Storage Temperature	-20°C to 70°C
Storage Humidity	10 to 90% RH (non-condensing)
Mechanical	
Dimension (HxWxD)	440mm x240mm x45mm
Weight	3.3kg
FAN Less	No
Heat dissipation	235.64 BPU/H
Power source	
AC Input	100V-240V
Certifications	
	EN61000-4-5 (for RJ45 Port, Surge 6KV)
	CE / Rohs / Reach

L2 Switching	
Spanning Tree	IEEE802.1D (STP)
	IEEE802.1W (RTSP)
	IEEE802.1S (MSTP)
VLAN	802.1Q VLAN
	Port-Based
	VLAN Entries 4K
	Private VLAN
	Voice VLAN
	Guest VLAN
	Q-in-Q
	802.1v Protocol VLAN
IEEE 802.3ad LACP	MAC-Based VLAN
	IP Subnet-Based VLAN
	Dynamic Trunk
	Static Trunk
GARP/GVRP	Yes
IGMP Snooping	Yes
MLD Snooping	Yes
L3 Features	
	DHCP Server
QoS Features	
Class of Service	Port Based
	802.1p
	DSCP
	TCP/UDP Port
Rate Limiting	Ingress
	Egress
Priority Queue Scheduling	WRR
	Strict Priority
Hardware Queues	8

## Security

<b>ACLs</b>	L2/L3/L4
	IPv6 Support
<b>Port Security (MAC-based)</b>	Yes
<b>IP Source Guard</b>	Yes
<b>Storm Control</b>	Yes
<b>RADIUS Authentication 802.1x</b>	Yes
<b>TACACS+ Authentication</b>	Yes
<b>HTTPs and SSL (Secured Web)</b>	Yes
<b>BPDU Guard</b>	Yes
<b>STP Root Guard</b>	Yes
<b>ARP inspection</b>	Yes
<b>DHCP Snooping</b>	Yes
<b>Loop Protection</b>	Yes

## Management

<b>DHCP</b>	Client
	Relay
	Option 66
	Option 67
	Option 82
<b>Event/Error Log</b>	Syslog
<b>Management Access Filtering</b>	SNMP
	Web UI
	Telnet
	SSH
<b>SNMP (v1, v2c, v3)</b>	Yes
<b>RMON (1, 2, 3 &amp; 9 Groups)</b>	Yes
<b>Software Upgrade</b>	Yes
<b>Configuration Export/Import</b>	Yes
<b>SFP DDM</b>	Yes
<b>Port Mirroring</b>	Yes
<b>Thermal Protection</b>	Yes
<b>LLDP (IEEE802.1AB)</b>	Yes
<b>IPv6 Management</b>	Yes
<b>NTP</b>	Yes

## Carrier Ethernet

<b>ERPS (ITU-T G.8032)</b>	Yes
----------------------------	-----

## Device Management System

<b>Traffic Monitoring</b>	WEB GUI/CLI/SNMP
<b>Cable Diagnostics</b>	Yes

## Associated Products

<b>GGM MSFPSX</b>	1000Base-SX SFP Module, MMF, LC connector, 550m
<b>GGM MSFPLX</b>	1000Base-LX SFP Module, SMF, LC connector, 10km
<b>GGM MSFP10GBLR</b>	10GBase-LR SFP+ Module, SMF OS2 (1310 nm), LC connector, 10 km
<b>GGM MSFP10GBSR</b>	10GBase-SR SFP+ Module, MMF OM3 (850 nm), LC connector, 300 m
<b>GGM DAC10G1M</b>	10GbE DAC SFP+ Cable - 1M
<b>GGM DAC10G2M</b>	10GbE DAC SFP+ Cable - 2M
<b>GGM DAC10G3M</b>	10GbE DAC SFP+ Cable - 3M
<b>GGM DAC10G7M</b>	10GbE DAC SFP+ Cable - 7M