

## Smart Switch 8 x Gigabit PoE ports + 2xSFP

8 x10/100/100 RJ45

POE 130W

Smart manageable

2 x SFP ports



GGM GS200 Web-managed Smart Switches series are designed to fit all the technical requirements of modern converged IP networks. Thanks to their large port versatility and their powerful Layer 2 features, GGM GS200 Smart Switches can deal simultaneously with Multimedia streaming, Multicast flux, security and any other services that could need a large bandwidth amount. GGM GS200 Web-managed Smart Switches offer an affordable Gigabit non-blocking network.

### Advanced Layer 2 Features

With their very much advanced Layer 2 features, the GGM GS200 Smart Switches can perfectly be integrated into modern IP Networks :

- Full network segmentation management with VLAN
- QoS features to optimize each IP flux
- Strong fault tolerance and redundancy with Spanning Tree technologies
- Loopback detection and quarantine of faulty links
- Cable diagnostics for an efficient network

### Strong network security

The GGM GS200 Smart Switches serie comes with the most valuable security technologies to protect your network against intrusion :

- 802.1x RADIUS authentication to ensure a reliable and strong users authentication on the network
- ACL feature to improve the network security and management
- ARP packet inspection to prevent ARP spoofing and networks hacking
- DHCP Snooping feature to prevent the use of rogue DHCP over the network

H/W	
CPU	Microsemi (Vitesse)
DRAM	1G
Flash memory	128M
Port Configuration	
10M/100M/1G RJ45 Port	8
100M/1G SFP Port	2
Console Port	RJ45
Total Ports	10
POE Function	
IEEE802.3at (PoE+ 30W)	Yes
IEEE802.3af (PoE 15.4W)	Yes
POE ports	8
Available PoE Power	130 W
HW Performance	
Switching Bandwidth	20Gbps
Forwarding Performance	14.88Mpps
MAC Address	8K
Jumbo Frames	9216 Bytes
Environmental	
Operating Temperature	0°C to 45 °C
Operating Humidity	10 to 90% RH (non-condensing)
Storage Temperature	-20°C to 70°C
Storage Humidity	10 to 90% RH (non-condensing)
Power source	
AC Input	100V-240V
Certifications	
	EN61000-4-5 (for RJ45 Port, Surge 6KV)
	CE / Rohs / Reach

L2 Switching	
Spanning Tree	IEEE802.1D (STP)
	IEEE802.1W (RTSP)
	IEEE802.1S (MSTP)
VLAN	802.1Q VLAN
	Port-Based
	VLAN Entries 4K
	Private VLAN
	Voice VLAN
	Guest VLAN
	Q-in-Q
	802.1v Protocol VLAN
	MAC-Based VLAN
	IP Subnet-Based VLAN
IEEE 802.3ad LACP	Dynamic Trunk
	Static Trunk
GARP/GVRP	Yes
IGMP Snooping	Yes
MLD Snooping	Yes
L3 Features	
	DHCP Server
QoS Features	
Class of Service	Port Based
	802.1p
	DSCP
	TCP/UDP Port
Rate Limiting	Ingress
	Egress
Priority Queue Scheduling	WRR
	Stri Proirity
Hardware Queues	8

## Security

ACLs	L2/L3/L4
	IPv6 Support
Port Security (MAC-based)	Yes
IP Source Guard	Yes
Storm Control	Yes
RADIUS Authentication 802.1x	Yes
TACACS+ Authentication	Yes
HTTPs and SSL (Secured Web)	Yes
BPDU Guard	Yes
STP Root Guard	Yes
ARP inspection	Yes
DHCP Snooping	Yes
Loop Protection	Yes

## Management

DHCP	Client
	Relay
	Option 66
	Option 67
	Option 82
Event/Error Log	Syslog
Management Access Filtering	SNMP
	Web UI
	Telnet
	SSH
PoE Management	Scheduling
	Auto-Checking
SNMP (v1, v2c, v3)	Yes
RMON (1, 2, 3 & 9 Groups)	Yes
Software Upgrade	Yes
Configuration Export/Import	Yes
SFP DDM	Yes
Port Mirroring	Yes
Thermal Protection	Yes
LLDP (IEEE802.1AB)	Yes
IPv6 Management	Yes
NTP	Yes

## Carrier Ethernet

ERPS (ITU-T G.8032)	Yes
---------------------	-----

## Device Management System

Traffic Monitoring	WEB GUI/CLI/SNMP
Cable Diagnostics	Yes

## Mechanical

Dimension (HxWxD)	279mm x 210mm x 44mm
Weight	2.4kg
FAN Less	Yes
Heat dissipation	Without POE: 105.87 BTU/H POE Full loaded : 549.82 BTU/H

## Associated Products

GGM MSFPSX	1000Base-SX SFP Module, MMF, LC connector, 550m
GGM MSFPLX	1000Base-LX SFP Module, SMF, LC connector, 10km
GGM MSFPFX2	100Base-FX SFP Module, MMF, LC connector, 2km
GGM MSFPFXSM	100Base-FX SFP Module, SMF, LC connector, 40km