



19" SERVERS FLOOR STANDING CABINET GIGARACK TYPE 250

GGM ALS42810C



The rigidity and the load capacity of the aluminium frame, the high level of equipment, the finish, the aesthetics ...

In brief, a real added value product ! The screwed assembly of the frame allows a complete dismantling of the cabinet, very practical in case of difficult access. To dissipate the heat it produces, a server needs a supply of fresh air on the front. The heated air will then be exhausted through the back of the server. To support this cooling process, it is therefore essential that the cabinet be equipped with perforated front and rear doors to allow the circulation of air flows and thus avoid the risk of overheating.

FEATURES

Type :	Server
Frame :	Aluminum, mechanically screwed (To be disassembled)
Mounting profiles :	Four 19" mounting profiles adjustable in depth (zinc plated), "U" markings, 9.5 x 9.5 mm perforations, Four 19" mounting profiles adjustable in depth (zinc plated), "U" markings, 9.5 x 9.5 mm perforations
Front door :	
Type A and B :	Reversible simple perforated door, can be opened up to 190°, locked by using multipoint swing handle with key lock (N°333)
Type C :	Double perforated door, can be opened up to 190°, locked by using multipoint swing handle with key lock (N°333)
Rear door :	
Type A :	Reversible simple perforated door, can be opened up to 190°, locked by using multipoint swing handle with key lock (N°333)
Type B and C :	Double perforated door, can be opened up to 190°, locked by using multipoint swing handle with key lock (N°333)
Side panels :	Two removable half panels (more ease in assembly / disassembly operations), designed for quick installation and be removable from the outside, locked by using latches and key locks (N° 333)
Roof :	Full, with rear pre-cut for cables entry (800 mm width cabinets are equipped with sides pre-cuts for cable entry)
Ground contact :	Adjustable feet (over 4 cm)
RAL :	9005 (Black)
Load capacity :	1500 kg
Earthing kit included :	No
Capacity :	42 U
Depth (mm) :	1000
Height :	2020 mm
Width :	800 mm

PART NUMBER	DESCRIPTION
GGM ALS42810C	19" Serv floor standing cabinet GIGARACK S250 42U 800 x 1000 mm type C - Black