



## RFID MIFARE EM READER

### GGM AXREMF1KW2M

#### READER MF/EM W32 IP66 CABLE 2M

The **GIGAMEDIA** proximity reader uses dual technology. It is able to read both the EM frequency 125kHz and Mifare Classic 13.56 MHz. This is very useful for the recovery and extension of an installation. It has a 32 bit Wiegand output. It can be connected to the GGM AXC product family (centralized solution) It can be installed indoors and outdoors. It has IP66 protection thanks to the resin coating of the electronic board. With its discreet design, it can be installed in most situations.

#### FEATURES

<b>Color :</b>	Black
<b>Power Consumption :</b>	25 mA
<b>Reader type :</b>	Rfid
<b>Output :</b>	Wiegand 32 bit
<b>Feeding range :</b>	9~24 VDC
<b>Rfid technology :</b>	Em
<b>Status led :</b>	Yes
<b>Accepted frequency :</b>	Em (125khz), mifare (13.56mhz)
<b>Operating temperature range :</b>	From -40 to 60°C
<b>Warranty period :</b>	24
<b>Cable length (m) :</b>	2
<b>Width :</b>	48 mm
<b>Height :</b>	120 mm
<b>Depth :</b>	20 mm

PART-NUMBER	DESCRIPTION
GGM AXREMF1KW2M	READER MF/EM W32 IP66 CABLE 2M