



GGM FCSKX6T5



Article features

- Stranded Core : Bare copper
- Shield : Braid cca - 85%
- Packaging : 500 m drum
- Outer sheath diameter (mm) : 6.1
- Insulation diameter (mm) : 3.7
- Impedance (ohms) : 75
- Insulation Material : Polyethylene
- NVP (%) : 66
- Bending radius (mm) : 50
- Jacket type : PVC

ETIM 9 features

- Paired co-axial cable : No
- 2 core co-axial cable (twinax) : No
- Inner conductor diameter : 1.2 mm
- Inner conductor material : Copper
- Inner conductor surface : Bare
- Conductor construction : Class 2 = stranded
- Outer conductor material : Other
- Outer conductor surface : Copper-plated
- Outer conductor type : Braiding
- Dielectric type : Solid PE (HD-PE)
- Armouring/reinforcement : None
- Rodent protected : No
- Specification material outer sheath : Polyethylene (PE)
- Jacket colour : Green
- Flame retardant according to IEC 60332-1-2 : No
- Flame retardant according to IEC 60332-3-21 (Cat A F/R) : No
- Flame retardant according to IEC 60332-3-22 (Cat A) : No
- Flame retardant according to IEC 60332-3-23 (Cat B) : No



- Flame retardant according to IEC 60332-3-24 (Cat C) : No
- Flame retardant according to IEC 60332-3-25 (Cat D) : No
- Low smoke according to EN IEC 61034-2 : No
- Halogen free according to EN IEC 60754-1 : No
- Halogen free according to EN IEC 60754-2 : No
- Halogen free according to EN IEC 60754-3 : No
- Reaction-to-fire according to EN 13501-6: Class : Eca
- Reaction-to-fire according to EN 13501-6: Smoke production : None
- Reaction-to-fire according to EN 13501-6: Flaming droplets/particles : None
- Reaction-to-fire according to EN 13501-6: Acidity : None
- UV resistant : No
- Impedance : 75 Ohm
- Cable OD : 6.1 mm
- Suitable for underground installation : No
- Approved type of underground installation : Underground installation tube
- Weight : 40.6 kg/km