



Cable 12 fibers OS2 9/125 μ m singlemode central loose tube gel-free Cable, indoor/outdoor use with hydro-blocking glass yarns anti-rodent protection, LSZH B2ca outer jacket, aqua colour
GGM FO12B9FRBLST



Central loose tube 250 μ m fibre optic cables, LSZH B2ca outer jacket.

Thanks to its gel-free construction and soft central tube, this cable allows for fast deployments by easing manipulations and reducing cable preparation time.

Product features

- Cable type : Loose tube 250 μ m
- Installation : indoor/outdoor
- Watertightness : Dry & longitudinal
- Fiber color code : IEC 60304
- Jacket : LSOH
- Euroclass : B2ca-s1a, d0, a1

Article features

- Bandwidth @1300 nm : N/A
- Bandwidth at 1310/1550 nm : Os2 $\geq$ 10,000 mhz/km
- Bandwidth @850 nm : N/A
- Bandwidth at 850 nm dmd : N/A
- Bandwidth at 850 nm emb : N/A
- Bending radius - minimum static (mm) : 92
- Bending radius - minimum dynamic (mm) : 122
- Cable weight (kg/km) : 45
- Central strength member : No
- Packaging : On cut
- Crush resistance (N) : 2000
- Diameter (mm) : 6
- Fire behaviour : EN 13501-6 : B2ca, s1a, d1, a1 ; EN 50575, EN 50399, EN 60332-1-2
- Marking : [Length] [GIGAMEDIA 12FO 9/125 OS2 CLT LSZH] [B2ca s1a d0 a1] [CLT FO CABLE FCTB004U] [Week/Year]
- Attenuation : At 1310 nm: os2 $\leq$ 0.36 db/km
- Fiber amount : 12
- Strength member : Reinforced glass yarns protection against rodents
- Jacket type : LSZH-FR
- Operating temperature : From -20°C to +60°C
- Tensile strength (n) : 1200
- Operating environment : Indoor / Outdoor



ETIM 9 features

- Fibre count : 12
- Structure : Central tube
- Fibre optic category : Single mode 9/125
- Category : OS2
- Strain relief : No
- Rodent protected : Yes
- Armouring/reinforcement : Other
- Material armouring : Other
- Specification material outer sheath : Other
- Jacket colour : Yellow
- Longitudinal water blocking cable : Yes
- Radial water blocking cable : Yes
- Metal free cable : Yes
- Cable geometry : Round
- Flame retardant according to IEC 60332-1-2 : Yes
- Flame retardant according to IEC 60332-3-21 (Cat A F/R) : Yes
- Low smoke according to EN IEC 61034-2 : Yes
- Halogen free according to EN IEC 60754-1 : Yes
- Halogen free according to EN IEC 60754-2 : Yes
- Reaction-to-fire according to EN 13501-6: Class : B2ca
- Reaction-to-fire according to EN 13501-6: Smoke production : s1a
- Reaction-to-fire according to EN 13501-6: Flaming droplets/particles : d0
- Reaction-to-fire according to EN 13501-6: Acidity : a1
- Oil resistant : No
- Resistant to chemicals : No
- UV resistant : Yes
- Cable OD : 6.1 mm
- Min. permitted bending radius, stationary application/permanent installation : 91.5 mm
- Max. tensile strength during installation : 1200 kN
- Suitable for underground installation : No
- Blowed cable : No
- Weight : 45 kg/km