



Cable 6 fibers OS2 9/125µm singlemode central loose tube gel-free Cable, indoor/outdoor use with corrugated steel tape anti rodent protection + hydro-blocking glass yarns, LSZH B2ca outer jacket, yellow colour

GGM FO6B9BCLST



Loose structure indoor/outdoor cable (250 µm fibres) steel armoured, LSOH. sheath Equipped with a steel reinforcement, it is resistant to crushing and can be buried directly. Available with an LSOH-FR B2ca outer sheath, it is suitable for the most demanding environments in terms of fire performance.

Product features

- Cable type : Loose tube 250 µm
- Installation : indoor/outdoor
- Watertightness : Dry & longitudinal
- Fiber color code : IEC 60304
- Jacket : LSOH
- Euroclass : B2ca-s1a, d0, a1

Article features

- Bandwidth @1300 nm : N/A
- Bandwidth at 1310/1550 nm : Os2 >= 10,000 mhz/km
- Bandwidth @850 nm : N/A
- Bandwidth at 850 nm dmd : N/A
- Bandwidth at 850 nm emb : N/A
- Bending radius - minimum static (mm) : 80
- Bending radius - minimum dynamic (mm) : 160
- Cable weight (kg/km) : 108
- Central strength member : No
- Packaging : 2000m
- Crush resistance (N) : 2000
- Diameter (mm) : 8
- Fire behaviour : EN 13501-6 : B2ca, s1a, d1, a1 ; EN 50575, EN 50399, EN 60332-1-2
- Marking : [Longueur] [GIGAMEDIA] [GGM FO6B9BCLST] [6FO 9/125 OS2 CLT CST LSZH] [B2ca s1a d1 a1] [CLT FO CABLE FCTBC006V] [Semaine/Année] [N°Lot]
- Attenuation : At 1310 nm: os2 <= 0.36 db/km
- Fiber amount : 6
- Strength member: : Corrugated steel tape + glass yarns protection against rodents
- Jacket type : LSZH-FR
- Operating temperature : From -40°C to +70°C
- Tensile strength (n) : 1000
- Operating environment : Indoor / Outdoor

ETIM 9 features

- Fibre count : 6
- Structure : Central tube
- Fibre optic category : Single mode 9/125
- Category : OS2
- Strain relief : No



- Rodent protected : Yes
- Armouring/reinforcement : Lap-screen
- Material armouring : Steel
- Specification material outer sheath : Other
- Jacket colour : Yellow
- Longitudinal water blocking cable : Yes
- Radial water blocking cable : Yes
- Metal free cable : No
- Cable geometry : Round
- Flame retardant according to IEC 60332-1-2 : Yes
- Flame retardant according to IEC 60332-3-21 (Cat A F/R) : Yes
- Flame retardant according to IEC 60332-3-24 (Cat C) : Yes
- Low smoke according to EN IEC 61034-2 : Yes
- Halogen free according to EN IEC 60754-1 : Yes
- Halogen free according to EN IEC 60754-2 : Yes
- Reaction-to-fire according to EN 13501-6: Class : B2ca
- Reaction-to-fire according to EN 13501-6: Smoke production : s1a
- Reaction-to-fire according to EN 13501-6: Flaming droplets/particles : d1
- Reaction-to-fire according to EN 13501-6: Acidity : a1
- Oil resistant : No
- Resistant to chemicals : No
- UV resistant : Yes
- Cable OD : 8 mm
- Min. permitted bending radius, stationary application/permanent installation : 160 mm
- Max. tensile strength during installation : 10 kN
- Suitable for underground installation : Yes
- Blowed cable : No
- Weight : 108 kg/km