



**1U empty and sliding patchpanel for 24 SC simplex / LC duplex adapters,
black colour + spooling accessories**

GGM GMT024SCSN



Bare sliding unequipped patch panel able to integrate up to 24 SC simplex or LC duplex multimode or monomode connectors

Product features

- Capacity : 12 to 48 fibers
- Port identification : Front numbering
- Number of cable entries : 6 x cable entries at the rear (2x 24 mm ; 2x 22 mm ; 2x 20 mm)
- Opening of the tray : 45°
- Fixing brackets : Adjustable depth
- Width (mm) : 483
- Depth (mm) : 225
- Height (mm) : 44
- Weight (kg) : 2.3
- Colour : Black
- Supplied accessories : 2 PG 13.5 cable glands, 6 coiling clips, 6 cable ties
- Optional accessory : SC simplex blanking plug (GGM OBTUSCSPLEX)

Article features

- Port density : 24

ETIM 9 features

- Number of connections : 24
- Number of slots : 24
- With front plate : Yes
- With housing : Yes
- With pigtails : No
- Fibre optic category : Singlemode and Multimode 50/125
- Outer connector : SC
- Inner connector : SC
- RAL : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Height (U) : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 224 mm