



Unmanaged 5-port Gigabit switch - Metal - ideal for extending your Gigabit network, with a reinforced metal switch (external power supply).

GGM GS05M



To correctly choose your switch, there is an interactive tool and video.

Article features

- Mdi/mdix auto-negotiation : Yes
- Non blocking : Yes
- Transfer method : Store and Forward
- Protocols : CSMA/CD
- Fanless : Yes
- Mac address table : 2
- Extended POE mode : No
- POE surge protection : 0
- Power supply type : External
- Max power consumption (W) : 5
- Heat Dissipation (Btu/h) : 17
- MTBF (H) : 80000
- Operating temperature range : 0 °C ~ +40° C
- Storage Temperature (°C) : -20 °C ~ +65° C
- Operating Humidity (% - non condensing) : 10% ~ 90%
- Storage Humidity (% - non condensing) : 5% ~ 95%

ETIM 9 features

- Ethernet : Yes
- Number of ports 10/100/1000 Mbps RJ45 : 5
- Power over Ethernet (PoE) : Other
- Mounting method : Desk type
- Layer 2 : No
- Layer 3 : No
- Manageable : No
- IP protection : IP30
- Height : 27 mm
- Width : 98 mm
- Depth : 70.7 mm
- Compatible with Grade2TV according to XP-C 90-483 : No
- Compatible with Grade3TV according to XP-C 90-483 : No