

UNMANAGEABLE SWITCH 10/100/1000

GGM GS1600 & GGM GS2400



GGM GS2400

16 or 24 10/100/1000Mbps

Rackable 19"

Store and Forward

With the **GGM GS2400** and **GGM GS1600** 24-Port & 16-Port Unmanaged Gigabit Ethernet Switch Expand your networking Store-and-forward. Easy to use these switches are rack-mountable Gigabit switch.

They supports auto MDI/MDIX and store-and-forward switching. There are a very large Gbps backplane bandwidth. They are ready for deployment in server rooms or offices with a need to keep serious network traffic flowing.


These switches let your network up to 24 or 16 Ethernet-enabled devices at speed up to 1000Mbps. This desktop switch supports Quality of Service feature that helps reduce jitter and lag with VOIP and games ! "Plug and Play" function assists you to set up easily.

PRODUCT FEATURES

- Complies with IEEE 802.3x full-duplex and flow control
- 16 or 24 10/100/1000Mbps ports connect to the workstation
- Supports Auto MDI/MDIX
- Supports NWA auto-negotiation function, auto-detect transfer data rate, UPnP, full-duplex, and automatically chooses the best network connectivity mode
- Supports IEEE802.3x full-duplex flow control, and half-duplex backpressure flow control
- 2 years warranty

BENEFITS

- Simple solution for expanding your networking
- Idea for VOIP and games
- Space saving design and installation options
- Easy to install and use
- High speed and excellent performance



PRODUCT SPECIFICATIONS

PROTOCOLS AND STANDARDS	TRANSMISSION METHOD	DIMENSIONS (WxDXH)
IEEE802.3, IEEE802.3u and IEEE802.3ab	Store-and-Forward	437 x 177 x 43mm (17.2" x 7.0" x 1.7")
INTERFACE	TRANSMISSION MEDIA	HOUSING MATERIAL
16 or 24 10/100/1000Mbps RJ45 Ports	10Base-T Cat.3 or 3e UTP 100Base-TX Cat.5 UTP 1000Base-T Cat.5e UTP	Steel
POWER SUPPLY	OPERATING TEMPERATURE	GROSS WEIGHT
AC 110-240V 50/60Hz input	32 to 104°F (0 to 40°C)	2.53 Kg
MAC ADDRESS TABLE SIZE	OPERATING HUMIDITY	CERTIFICATE
8K	10 to 90% Non condensing	CE, RoHS
PACKET BUFFER	STORAGE TEMPERATURE	WARRANTY
2Mb	-40 to 158°F (-40 to 70°C)	24 months
BACKPLANE BANDWIDTH	STORAGE HUMIDITY	
32Gbps	5 to 90% Non condensing	

PART NUMBER

P/N	DESCRIPTION
GGM GS1600	Switch 16 ports 10/100/1000 rackable 19"
GGM GS2400	Switch 24 ports 10/100/1000 rackable 19"

VOTRE INTERLOCUTEUR CONSEIL