



Patch cord RJ45 INITIO Category 5E U/UTP unshielded 26AWG (7/0,16) LSHF, molded boots, Grey 10M

GGM INIC5EU10MGY



INTIO Category 5E U/UTP patchcords is an economical alternative offered for Network, efficient for high speed data transmission, phone application and work area. High performances that are complying with the effective cabling standards (ISO-IEC / EIA-TIA) They are suitable for transmission frequencies up to 100 MHz.

All patchcords are supplied with molded boots.

Product features

- Applications : IEEE802.3 : 2.5GBase-T, 1000Base-T, 100Base-Tx, 10Base-T IEEE 802.3af/at/bt (PoE/PoE+/4PPoE)
- Shielding : U/UTP
- Category : 5E
- Standards : ANSI/TIA-568-C.2 ; EN 50173 ; ISO/IEC 11801
- Outersheath diameter : 5
- Frequency range : From 0 to 100 Mhz
- Impedance : 100
- Gauge (awg) : 26
- Boot : Molded
- Conductor type : Stranded wires
- NVP (%) : 67
- Cable schematics : 568A/B
- Fire behaviour : N/A
- Connector type : RJ45
- Sheath type : LSHF

Article features

- Outer jacket colour : Grey
- Packaging : By piece

ETIM 9 features

- Shield type : U/UTP
- Length : 10 m
- Connector A : RJ45 8(8)
- Connector B : RJ45 8(8)
- Jacket colour : Grey
- Snagless : Yes
- Boot colour : Grey



- Fire retardant : Yes
- Oil resistant : No
- Number of pairs : 1x4
- AWG : 26
- Wire scheme : 1:1
- NVP : 67 %
- Compatible with Grade2TV according to XP-C 90-483 : No
- Compatible with Grade3TV according to XP-C 90-483 : No