



PATCH cord INITIO RJ45 568B category 6A S/FTP 10G CHANNEL ISO/IEC 11801 et ANSI/TIA-568.2-D 4X2XAWG26 (7*0,16mm) SHIELDED LSZH 1M, overmolded White RAL9003

GGM INIC6ASF1MWH



INITIO CAT6A S/FTP patch cords are a cost-effective solution for patching Ethernet applications up to 10Gigabit/s, offering an excellent performance/price ratio without compromising on the compliance with standards.

- Applications : IEEE802.3 : 10GBase-T, 5GBase-T, 2.5GBase-T, 1000Base-T, 100Base-Tx, 10Base-T IEEE 802.3af/at/bt (PoE/PoE+/4PPoE)
- Shielding : S/FTP
- Category : 6A
- Standards : ANSI/TIA-568.2-D ; EN 50173 ; ISO/IEC 11801
- Outersheath diameter : 5,9
- Frequency range : From 0 to 500 Mhz
- Impedance : 100
- Gauge (awg) : 26
- Boot : Molded slim boots
- Conductor type : Stranded copper
- NVP (%) : 80
- Cable schematics : Right
- Fire behaviour : No
- Connector type : RJ45
- Sheath type : LSZH
- Outer jacket colour : White
- Packaging : By piece
- Shield type : S/FTP
- Length : 1 m
- Connector A : RJ45 8(8)
- Connector B : RJ45 8(8)
- Jacket colour : White
- Snagless : Yes
- Boot colour : White
- Fire retardant : Yes
- Oil resistant : No
- Number of pairs : 1x4
- AWG : 26
- Wire scheme : 1:1
- NVP : 80 %
- Compatible with Grade2TV according to XP-C 90-483 : No
- Compatible with Grade3TV according to XP-C 90-483 : No