



Tactile office IP microphone GGM IPAMIC



This tactile desktop microphone allows any network equipment to be called (amplifier, loudspeaker, intercom, ...). It connects to the network via its RJ45 port. It is equipped with a 7" colour touch screen. It has a numeric keyboard as well as one-touch buttons for calling groups. It supports full duplex communications and integrates an echo cancellation module. It is possible to connect a microphone with the 3.5 mm inputs. It is possible to define user profiles with customised touches depending on users and their needs.

Product features

- Audio Format : MP3
- Transmission rate : 100mbps
- Audio mode : 16 bit cd quality

Article features

- Continuous recording : 80 Hz~16 KHz +1/-3 dB
- Distortion :
- Phone Out power and impedance (Ohms) : 32
- Line input sensitivity (mV) : 350
- Line out output voltage (mv) : 1000
- Line output impedance (ohms) : 470
- Microphone input sensitivity (mV) : 10
- Operating temperature range : From 5 to 40°C
- Panel resolution : 800x480
- RSB : > 65 db
- Sampling : 8k ~ 48KHz
- Screen size (inch) : 7
- Short circuit input : Dry contact
- Short circuit output : Max 30 vdc /1a or contact s
- Speaker impedance and power : 4 ohm 2w
- Power supply : 24 vdc/2a
- Type of keyboard : Virtual qwerty
- Type of screen : 65k colors

ETIM 9 features

- With gooseneck : Yes
- Technique : Capacitor microphone
- Stereo : No
- Wireless : No
- Sensitivity : -47 dB



- With stand holder : No
- Watertight : No
- With LCD indication : Yes
- With lock function : Yes
- With wind protection : No