



IP mixer amplifier 500 W with 100 V output **GGM IPAP1500**



Enter the world of IP sound systems Develop your sound system towards an IP solution while still keeping your old loud speakers. This 1 zone IP mixer amplifier has an RJ45 input. It connects to the building IT network and is able to receive data from the centralised management software. It integrates a class D amplifier with a 4-16 Ohm output or a constant 70/100 V voltage Its ultra rapid processor allows a start-up in less than 1 second It also has local inputs EMC, AUX and MIC. First stage in your building mutation. This solution provides step by step migration of your cosy sound system.

Product features

· Auxiliary input: Yes Auxiliary output : Yes

• Operating temperature : From 5°C to 40°C

• Supply voltage: 220 vac

• Network interface : RJ45 100 Mbps

Audio format : MP3

• Protocols: TCP/IP, UDP, IGMP (multicast)

Article features

• Emc input : Yes

• Speaker output : 4-6 ohm constant resistance

 Mounting style : 2u rackmount • Microphone input: Yes • Total power (w): 500 • Weight (kg): 18

ETIM 9 features

· Model: Mixing amplifier

• Freestanding : Yes

• Rack-assembly possible : Yes

• 70 V amplifier: Yes

• 100 V amplifier : Yes

• Music power at 70 V: 500 W

• Music power at 100 V: 500 W

· Inputs with priority switching: Yes

• Number of analogue inputs : 2 • Number of analogue outputs : 1

• Number of loudspeaker outputs : 1

• Number of RCA audio sockets: 6

• Number of supported paging zones : 1









• Number of microphone inputs : 1

• With display : Yes • With VU meter : No • With remote control : Yes • Operation by app : Yes • Handling with software : Yes • With backup battery : No

• Number of Ethernet-connections : 1

• Colour : Black • Material : Metal • Width: 484 mm • Height: 132 mm • Depth : 359 mm