



IP mixer amplifier 350 W 8 zones with 100 V output GGM IPAP8350



The multi-zone IP mixer amplifiers allow up to 8 100 V lines to be connected to the same product. They are of 19 inch format and integrate a 3.4 inch LCD screen showing current local tasks. An industrial quality processor gives great stability, availability and rapidity when starting up and when operating. This product is integrated into the IT network. It integrates a network module compatible with TCP/IP, UDP, IGMP protocols and supplies CD type sound quality (16 bit stereo). It has a loud speaker constant voltage output, 100 V as well as an EMC priority input, an AUX input/output and a MIC input. With the management software, it is possible for each of the zones (together or separately), to call them, affect planned tasks to them or to send messages (diffusion, alarm, messages).

Product features

- Number of areas : 8
- Operating temperature : From 5°C to 40°C
- Supply voltage : 220 vac
- Network interface : RJ45 100 Mbps
- Audio format : MP3
- Protocols : TCP/IP, UDP, IGMP (multicast)

Article features

- Auxiliary output : Yes
- Power Consumption : Max 540w
- Emc input : Yes
- Speaker output : 100v constant voltage
- Mounting style : 2u rackmount
- Microphone input : Yes
- Total power (w) : 350
- Weight (kg) : 15.5

ETIM 9 features

- Model : Mixing amplifier
- Freestanding : Yes
- Rack-assembly possible : Yes
- 100 V amplifier : Yes
- Music power at 100 V : 350 W
- Inputs with priority switching : Yes
- Number of analogue inputs : 2
- Number of analogue outputs : 1
- Number of loudspeaker outputs : 8
- Number of RCA audio sockets : 6



- Number of supported paging zones : 8
- Number of microphone inputs : 1
- With display : Yes
- With VU meter : No
- With remote control : Yes
- Operation by app : Yes
- Handling with software : Yes
- With backup battery : No
- Number of Ethernet-connections : 1
- Colour : Black
- Material : Metal
- Width : 484 mm
- Height : 132 mm
- Depth : 359 mm