



Wall mounted IP amplifier 2 x 15 W and wireless micro GGM IPAW215DMP



Wall mounted amplifiers provide a localised and economical sound system for a room. They are discrete and have 2 x 15 W 8 Ohm LS outputs. They use IP connections to recover music and messages from the IP network. They also have an AUX input and MIC input for more local use. These solutions are ideal for classroom sound systems, meeting rooms and sports halls.

Product features

- Network interface : RJ 45 100Mbps input
- Operating temperature : From 5°C to 40°C
- Power supply : 220 vac
- Audio format : MP3
- Protocols : TCP/IP, UDP, IGMP (multicast)

Article features

- Auxiliary input : Yes
- Power Consumption : Max
- Speaker output : 2 x 15w 8 ohm
- Microphone input : Yes
- Screen size (inches) : 3.4
- Mounting style : Surface-mount
- Weight (kg) : 0.9

ETIM 9 features

- Freestanding : Yes
- Rack-assembly possible : No
- 50 V amplifier : No
- 70 V amplifier : No
- 100 V amplifier : No
- Music power at 8 Ohm : 30 W
- Inputs with priority switching : Yes
- Number of analogue inputs : 1
- Number of loudspeaker outputs : 2
- Number of supported paging zones : 1
- Number of microphone inputs : 1
- With display : Yes
- With VU meter : No
- With remote control : Yes
- Operation by app : Yes
- Handling with software : Yes



- With backup battery : No
- Number of Ethernet-connections : 1
- Colour : Black
- Material : Metal
- Width : 134 mm
- Height : 170 mm
- Depth : 45 mm