

GGM IPCEB2F28

IPBULLET2MP LENS 2.8 mm

H265 / H264

2 Mégapixels

IR 20M

Digital WDR

Fixed lens 2.8mm

IP₆₆













GIGAMEDIA camera provides an excellent ratio price/performance for your security installation.

The GGM IPCEB2F28 is discrete and has large angle of view. Infrared to light up to 20 m and the quality of the night vision is ensured by SMD LED. This camera can be installed in indoor or outdoor environment and will always provide you good picture quality in day or night. It embbeds intelligent functions to perform performance of your installation.

PICTURE

SC2235H, 1/2.7" Progressive CMOS **SENSOR** Fixed Lens 2.8 mm F1.85±10% LENS 103° Horizontal **ANGLE** SENSITIVITY Color 0.1lux @ F1.2(AGC ON); B/W 0 lux @ IR ON Digital WDR Yes DAY/NIGHT 20M INFRARED 25 fps @ 1920x1080 **FPS IMAGE SETTING** SHUTTER SPEED 1/5 ~ 1/20000s

ALARM

 MOTION DETECTION
 Yes

 MANUAL TRIGGER
 Yes

 REBOOT
 Yes

 RECORDING NOTIFICATION
 Yes

 TEMPERING DETECTION
 Yes

GENERAL INFORMATION

 DIMENSIONS
 Ø 69X 138.24mm

 WEIGHT
 235 g

 WORKING TEMPERATURE
 -30° + 55° c

 STORAGE TEMPERATURE
 -30° + 60° c

NETWORK

INTERFACE
STREAMS
2 Simultaneous streams
COMPRESSION
CLIENT CONNEXIONS
PROTOCOLS
10
TCP / IP, HTTP, DHCP, DNS, DDNS, RTP / RTSP, PPPOE, SMTP, NTP, UPNP, SNMP, HTTPS, FTP.

SYSTEM

 CPU
 313E

 FLASH
 16M

 RAM
 512M

 COMPATIBILITY
 WINDOWS, MAC

 MANAGEMENT SOFTWARE
 Surveillance client

 MOBILE APP
 GGM VIEW

POWER SUPPLY

ONVIF

802 3af POE **POWER** 12V 1A CONSUMPTION 7w max MORE INFO SD CARD STORAGE No ALARM IN/OUT No No **AUDIO** No **BNC OUT** IP RATE **IP66 CERTIFICATIONS** CE, FCC, RoHS, EMC

Version 2.6



PICTURE SETTING, IMAGE CONTROL



ACCESSORIES

Junction Box: GGM IPCBJ011



Junction Box (wall mount only):

GGM IPCBJ010



Wall mount: GGM IPCBJ008

