



## CENTRAL ACCESS CONTROL PANEL

### GGM KITAX2DS



2 Readers securized access control kit + 10 cards. Web manageable

The KITAX2DS is an access control kit that can be used to secure two doors for single access or one door for entry/exit. The solution offers a high level of security through the use of RS485 and Desfire EV2 protocols. In order to reduce the investment associated with a high-security installation, a **GIGAMEDIA** private key is integrated into the solution. This makes it possible to get rid of additional software that can considerably increase the bill on a small project.

This kit consists of an IP control unit, two secure readers (GREADER) and 10 badges (GCARD). It is possible to upgrade your installation up to 42 drives via 4-door expansion modules (AXC4DEXTEVO) in web management only. The hub supports up to 5000 users in web mode and 50,000 with management in ACS software.

Many features integrated into the product will allow you to be efficient in the configuration and use of the solution.

The drive has IK10 and IP65 protection. It has an anti-breach system to remove security keys in the event of a break-in. It comes with a 3m cable for easy connection in the false ceiling.

An ideal solution to

provide a real security response to current threats, the access control kit is the ideal solution for securing all your projects.

#### FEATURES

<b>Automation relay, automation scenarios :</b>	Yes
<b>Fixing :</b>	Din rail Or SCrewing
<b>Max number of events :</b>	15000
<b>Maximum number of users :</b>	50000
<b>Power supply :</b>	12 vdc
<b>Supported reader protocols :</b>	Wiegand/clockand dATa/rs485

<b>Terminal block :</b>	Up to 3 mm withdrawable section
<b>Controller type :</b>	Central on ip (fixed ip /dhcp)
<b>Standalone :</b>	No
<b>Networkable :</b>	Yes
<b>PC-binding :</b>	Yes
<b>Max. number of doors :</b>	2
<b>Type of interface :</b>	Ethernet
<b>Max. number of persons :</b>	5000
<b>Reading strategy :</b>	Data medium
<b>Signalling :</b>	Light signal
<b>Mounting method :</b>	Surface mounted (plaster)
<b>Operating voltage at DC :</b>	12 - 12
<b>Degree of protection (IP) :</b>	IP65
<b>Colour :</b>	Black
<b>Model :</b>	Reader
<b>Width :</b>	42.2 mm
<b>Height :</b>	111.5 mm
<b>Depth :</b>	22 mm
<b>Compatible with Apple HomeKit :</b>	No
<b>Compatible with Google Assistant :</b>	No
<b>Compatible with Amazon Alexa :</b>	No
<b>IFTTT support available :</b>	No

PART-NUMBER	DESCRIPTION
GGM KITAX2DS	2 readers securized access control kit + 10 cards. Web manageable