

IP 54 FLEXIBLE FIBER DISTRIBUTION BOXES

GGM ODBxxWM



GGM ODB48WM



GGM ODB16WM

Compact and modular, these wall mount boxes are suitable for an indoor or outdoor use with a density of up to 48 fibers.

APPLICATIONS

- FTTx (MDU, consolidation point...)
- Building premises
- Industry

MAIN FEATURES

- UV resistant ABS plastic boxes
- IP54 / IK10
- 16 to 48 fibers (SC simplex)
- Connection with adaptors (SC simplex or LC duplex) or fusion splices
- Integrated splice trays & spooling cable management
- Suitable for G652 & G657 fibers
- GGM ODB16WM : possibility to install 2 splitters (1x8 or 1x16)
- Lockable with a key (included)
- RAL7035 grey
- Dimensions: 250 x 90 x 380 mm
- UL 94 V0 flammability rate
- Temperature: -40°C to +70°C
- Supplied with 2 splice trays (fusion), fixing accessories & user guide

	16 FIBERS VERSION	48 FIBERS VERSION
P/N	GGM ODB16WM	GGM ODB48WM
Cable glands	NO	2x PG29 + 2x PG16
Cable entries	10 (Ø 5 mm max.)	4
Dimensions	250 x 90 x 380 mm	250 x 90 x 380 mm
Weight	2,1 kg	2,2 kg