

WALL MOUNT SPEAKER GGM PABW30PB & GGM PABW30PW



This wall mount speaker include 70/100 V transformer to avoid line loss and increase transmission distance. Several speakers can be connected in parallel mode.

MAIN FEATURES

PART NUMBER	GGM PABW30PB	GGM PABW30PW
Power tap @ 100 V	3,75 W, 7,5 W, 15 W, 30 W	3,75 W, 7,5 W, 15 W, 30 W
Power tap @ 70 V	1,9 W, 3,75 W, 7,5 W, 15 W	1,9 W, 3,75 W, 7,5 W, 15 W
Impedance	2,6 kΩ / 1,3 kΩ / 670 Ω / 330 Ω / 165 Ω	2,6 kΩ / 1,3 kΩ / 670 Ω / 330 Ω / 165 Ω
Input	70 V / 100 V / 8 Ω	70 V / 100 V / 8 Ω
Sensitivity SPL (1W/1m)	90 dB	90 dB
Sensitivity max. SPL (Rated W/1m)	103 dB	103 dB
Frequency response (-10 dB)	100-18 kHz	100-18 kHz
Material	Baffle: ABS, black Grille: steel, black	Baffle: ABS, white Grille: steel, white
Speaker	5"x1	1,5"x1
Dimension	285 x180 x186 mm	285 x180 x186 mm
Weight	2,7 kg	2,7 kg