



Preloaded 1U black patchpanel with 6 SC duplex OS2 adapters with ceramic ferule + 12 semi-tight buffer easy-strip colored pigtails + splice tray, spooling accessories, PG13,5 Cable gland
GGM TIREQ6SC09



Sliding patch panel equipped with 6 SC duplex monomode connectors + 12 SC OS2 pigtails

Product features

- Number of ports : 24 port
- Port identification : Numbering and marking space available on the front
- Number of cable entries : 6 x cable entries at the rear (2x 24 mm ; 2x 22 mm ; 2x 20 mm)
- Quick installation : Opening up to 45° for easy handling
- Fixing brackets : Adjustable depth
- Width (mm) : 483
- Depth (mm) : 224
- Height (mm) : 44
- Weight (kg) : 2.7
- Colour : Black
- Supplied accessories : Splice tray, 2 cable glands (PG 13.5), bunny clips

Article features

- Accessories included : 1 cable gland (PG 13.5), 1 splice management kit for 24 fusion splices, 8 bunny clips
- Cable entries : 2 x 20 mm + 4 x 10 mm
- Pigtails : 12 colours coding OS2 pre-loaded

ETIM 9 features

- Number of connections : 24
- Number of slots : 6
- With front plate : Yes
- With housing : Yes
- With pigtails : Yes
- Fibre optic category : Single mode
- Fibre type : OS2
- APC : No
- Outer connector : SC duplex
- Inner connector : SC duplex
- RAL : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Height (U) : 1
- Height : 44 mm



- Width : 483 mm
- Depth : 200 mm