



Preloaded 1U black patchpanel with 12 LC duplex OS2 blue adapters with ceramic ferule + spooling accessories, splice management support, PG13,5

Cable gland

GGM TIRRA12LC09



Sliding optical drawer equipped with 12 LC duplex monomode connectors

Product features

- Number of ports : 24 port
- Port identification : Numbering and marking space available on the front
- Number of cable entries : 6 x cable entries at the rear (2x 24 mm ; 2x 22 mm ; 2x 20 mm)
- Quick installation : Opening up to 45° for easy handling
- Fixing brackets : Adjustable depth
- Width (mm) : 483
- Depth (mm) : 224
- Height (mm) : 44
- Weight (kg) : 2.7
- Colour : Black
- Supplied accessories : Splice tray, 2 cable glands (PG 13.5), bunny clips

Article features

- Accessories included : 1 cable gland (PG 13.5), 1 splice management kit for 24 fusion splices, 8 bunny clips
- Cable entries : 2 x 20 mm + 4 x 10 mm
- Pigtails : N/A

ETIM 9 features

- Number of connections : 24
- Number of slots : 12
- With front plate : Yes
- With housing : Yes
- With pigtails : No
- Fibre optic category : Single mode
- Fibre type : OS2
- APC : No
- Outer connector : LC-Duplex
- Inner connector : LC-Duplex
- RAL : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Height (U) : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 200 mm