



Preloaded 1U black patchpanel with 6 LC duplex OM2/OM3 grey adapters with ceramic ferule + spooling accessories, splice management support, PG13,5

Cable gland

GGM TIRRA6LC50



Sliding patch panel equipped with 6 LC duplex multimode connectors.

Product features

- Cable entries : 2x20mm + 4x10mm
- Depth (mm) : 200
- Height (mm) : 44
- Number of ports : 24
- Port identification : Numbering and marking space available on the front
- Quick installation : Opening up to 45° for easy handling
- Supplied accessories : Splice tray, 2 cable glands (PG 13.5), bunny clips

Article features

- Accessories included : 1 cable gland (PG 13.5), 1 splice management kit for 24 fusion splices, 8 bunny clips
- Width (mm) : 483
- Weight (kg) : 2.6

ETIM 9 features

- Number of connections : 24
- Number of slots : 3
- With front plate : Yes
- With housing : Yes
- With pigtails : No
- Fibre optic category : Multi mode 50/125
- APC : No
- Outer connector : LC-Duplex
- Inner connector : LC-Duplex
- Colour : Black
- RAL : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Height (U) : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 200 mm