




CAT6 U/UTP LSZH-FR/PE CABLE

GGM C6U4PFRWBPET3



CAT6 5 Gigabit/s performance

LSZH-FR / PE double jacket

Gel-free waterblocking tape

APPLICATIONS

- ▶ **IEEE802.3:** 5GBase-T, 2.5GBase-T, 1000Base-T (Gigabit Ethernet), 100Base-Tx, 10Base-T
- ▶ **IEEE 802.3af:** PoE
- ▶ **IEEE 802.3at:** PoE+
- ▶ **IEEE 802.3bt:** 4 PPoE

This cable has been designed to exceed the requirements of ISO/IEC 11801 and EN 50173 for Category 6 components. The performance headroom provided makes it a reliable and safe choice to support all class E applications including 5 Gigabit Ethernet and PoE.

With its LSZH-FR/PE double jacket, it is particularly suitable for outdoor installations, while its waterblocking tape offers gel-free watertightness, thus reducing cable preparation time.

It can also be installed indoors once the PE outer jacket has been withdrawn.

MECHANICAL CHARACTERISTICS


ITEM	JACKET	CONDUCTORS	INSULATION (MM)	EXTERNAL DIAMETER (MM)	GROSS WEIGHT (KG)	BENDING RADIUS (MM)	INSTALLATION TENSION (N)
4	LSZH-FR / PE	AWG23	1	6 / 8.2 (LSZH-FR/PE)	19.5	65.6	110

- ▶ Temperature rating
0 °C to +50 °C (installation)
-20 °C to +60 °C (operating)
- ▶ Standards:
ANSI/TIA-568-2-D (CAT6), EN50173 CAT6,
ISO/IEC11801 CAT6, IEC 61156-5 : Ed.2.0
- ▶ Fire behaviour (inner jacket):
EN 13501-6: Cca-s1a, d1, a1
EN 50575, EN 50399, EN 60332-3
- ▶ Crush and moisture resistant according to
EN 50289-3 & EN 60811-501

P/N	DESCRIPTION	PACKAGING
GGM C6U4PFRWBPET3	CAT6 4 pairs AWG23 U/UTP LSZH-FR/PE outdoor - black	Drum 305 m

CABLE MARKED

GIGAMEDIA C6U4PFRWBPET3 EN50173 CAT6 U/UTP LSZH-FR / PE WATER BLOCKED OUTDOOR CABLE NVP 67% 4 PAIRS 23AWG (batch #) (lot #) xxx M



TRANSMISSION PERFORMANCE

FREQUENCY (MHZ)	IMPEDANCE (Ω)	ATTENUATION (DB) MAX	NEXT (DB) MIN	PSNEXT (DB) MIN	ACRF (DB) MIN	PSACRF (DB) MIN	RETURN LOSS (DB) MIN	PROPAGATION DELAY (NS) MAX	DELAY SKEW (NS) MAX
4	100 ±15	3.8	66.3	63.3	55.8	52.8	23.0	552.0	45
10		6.0	60.3	57.3	47.8	44.8	25.0	545.4	
16		7.6	57.2	54.2	43.7	40.7	25.0	543.0	
20		8.5	55.8	52.8	41.8	38.8	25.0	542.0	
31.25		10.7	52.9	49.9	37.9	34.9	23.6	540.4	
62.5		15.4	48.4	45.4	31.9	28.9	21.5	538.6	
100		19.8	45.3	42.3	27.8	24.8	20.1	537.6	
125		22.4	43.8	40.8	25.9	22.9	19.4	537.2	
200		29.0	40.8	37.8	21.8	18.8	18.0	536.6	
250		32.8	39.3	36.3	19.8	16.8	17.3	536.3	

- ▶ Segregation class B
- ▶ Insulation resistance (500 V): ± 5000 MΩ/km
- ▶ Resistance unbalance: ≤ 2 % at 20 °C
- ▶ Velocity of propagation: 67 %

P/N	DESCRIPTION	PACKAGING
GGM C6U4PFRWBPET3	CAT6 4 pairs AWG23 U/UTP LSZH-FR/PE outdoor - black	Drum 305 m