



Patch cord Category 6A Slim U/FTP shielded 32AWG RJ45 50 micron inches gold plating with Ultra short slim snagless colored boots, 10G OUTDOOR 30M PE OD : 5.7 mm, ISO/IEC 11801, EN 50173, IEC 61156-5, ANSI/TIA-568.2-D

**GGM CAT6ASF30MPE**



Outdoor Cat6A S/FTP RJ45 Patch cords with polyethylene (PE) are designed for outdoor use, providing reliable and fast network connectivity for outdoor applications. These cables are built to withstand outdoor environmental conditions such as moisture, extreme temperatures, and UV rays, ensuring optimal performance even in challenging environments.

Available in CAT6A S/FTP AWG27 from 5m to 30m, black outer jacket color

## Product features

- Applications : IEEE802.3 : 10GBase-T, 5GBase-T, 2.5GBase-T, 1000Base-T, 100Base-Tx, 10Base-T IEEE 802.3af/at/bt (PoE/PoE+/4PPoE)
- Shielding : S/FTP
- Category : 6A
- Standards : ANSI/TIA/EIA-568-B.2-1 ISO/IEC 11801 2nd édition EN50173-1
- Outersheath diameter : 3.8
- Frequency range : From 0 to 550 Mhz
- Impedance : 100
- Gauge (awg) : 27
- Boot : Yes
- Conductor type : Stranded wires
- NVP (%) : 78
- Cable schematics : Right
- Fire behaviour : N/A
- Connector type : RJ45
- Sheath type : HDPE, UV resistance

## Article features

- Outer jacket colour : Black
- Packaging : By piece

## ETIM 10 features

- Cable type : S/FTP
- Length : 30 m
- Type of connector connection 1 : RJ45 8(8)
- Type of connector connection 2 : RJ45 8(8)
- Colour outer sheath : Black
- Anti-kink sleeve : Moulded-on
- Locking lever : Yes



- Colour anti-kink sleeve : Black
- Fire retardant version : No
- Oil resistant according to EN IEC 60811-404 : No
- AWG-size : 27
- Pin assignment : 1:1
- NVP value : 78 %