



19" CABLING FLOOR STANDING CABINET GIGARACK TYPE 250 GGM AL3966N



39 U
600 X 600 mm
Black

The rigidity and the load capacity of the aluminium frame, the high level of equipment, the finish, the aesthetics ...

In brief, a real added value product ! The screwed assembly of the frame allows a complete dismantling of the cabinet, very practical in case of difficult access.

FEATURES

Type :	Cabling
Frame :	Aluminum, mechanically screwed (To be disassembled)
Mounting profiles :	Two 19" mounting profiles adjustable in depth (zinc plated), "U" markings, 9.5 x 9.5 mm perforations
Front door :	Reversible securit glass door with side profiles, can be opened up to 190°, locked by using swing handle with key lock (N°333)
Rear panel :	Removable, designed for quick installation and be removable from the outside, locked by using 2 latches and key lock (N° 333)
Side panels :	Removable, designed for quick installation and be removable from the outside, locked by using 2 latches and key lock (N° 333)
Roof :	Full, with rear pre-cut for cables entry (800 mm width cabinets are equipped with sides pre-cuts for cable entry)
Base :	Open, bottom plate available as an option
Ground contact :	Adjustable feet (over 4 cm)
Protection :	IP 20
Load capacity :	1500 kg
Earthing kit included :	No
Capacity :	39 U
Depth :	600 mm
Height :	1880 mm
Width :	600 mm

PART NUMBER	DESCRIPTION
GGM AL3966N	19" Cabling floor standing cabinet GIGARACK S250 39U 600 X 600 mm - Black