



GGM FCSRG59BUST



Article features

- Shield : Braid cca - 85%
- Packaging : Reel of 1000 m
- Outer jacket colour : Black
- Outer sheath diameter (mm) : 6.1
- Insulation diameter (mm) : 3.66
- Impedance (ohms) : 75
- Jacket type : PVC
- NVP (%) : 66
- Bending radius (mm) : 30
- Conductors size : 0,58 mm wires
- Conductor type : Copper

ETIM 10 features

- Paired co-axial cable : No
- 2 core co-axial cable (twinax) : No
- Diameter inner conductor : 0.58 mm
- Inner conductor material : Copper
- Inner conductor surface : Bare
- Inner conductor category : Class 2 = stranded
- Outer conductor surface : Copper-plated
- Type of outer conductor : Braiding
- Dielectric : Solid PE (HD-PE)
- Armouring/reinforcement : None
- With rodent protection : No
- Material outer sheath : Polyvinyl chloride (PVC)
- Specification material outer sheath : Polyethylene (PE)
- Colour outer sheath : Black
- Flame retardant according to IEC 60332-1-2 : No
- Flame retardant according to IEC 60332-3-21 (Cat A F/R) : No
- Flame retardant according to IEC 60332-3-22 (Cat A) : No
- Flame retardant according to IEC 60332-3-23 (Cat B) : No
- Flame retardant according to IEC 60332-3-24 (Cat C) : No
- Flame retardant according to IEC 60332-3-25 (Cat D) : No
- Low smoke according to EN IEC 61034-2 : No
- Halogen free according to EN IEC 60754-1 : No
- Halogen free according to EN IEC 60754-2 : No
- Halogen free according to EN IEC 60754-3 : No
- Reaction-to-fire according to EN 13501-6: Class : Eca
- Reaction-to-fire according to EN 13501-6: Smoke production : None
- Reaction-to-fire according to EN 13501-6: Flaming droplets/particles : None
- Reaction-to-fire according to EN 13501-6: Acidity : None
- Characteristic impedance : 75 Ohm
- Outer diameter approximate : 6.1 mm
- Suitable for underground installation : No
- Approved type of underground installation : Underground installation tube
- Permitted cable outer temperature during assembling/handling : -20 - 70
- Permitted cable outer temperature after assembling without vibration : -20 - 70