



1U empty and sliding patchpanel for 24 SC simplex / LC duplex adapters, black colour + spooling accessories

GGM GMTO24SCSN



Bare sliding unequipped patch panel able to integrate up to 24 SC simplex or LC duplex multimode or monomode connectors

Product features

- Capacity : 12 to 48 fibers
- Port identification : Front numbering
- Number of cable entries : 6 x cable entries at the rear (2x 24 mm ; 2x 22 mm ; 2x 20 mm)
- Opening of the tray : 45°
- Fixing brackets : Adjustable depth
- Width (mm) : 483
- Depth (mm) : 225
- Height (mm) : 44
- Weight (kg) : 2.3
- Colour : Black
- Supplied accessories : 2 PG 13.5 cable glands, 6 coiling clips, 6 cable ties
- Optional accessory : SC simplex blanking plug (GGM OBTUSCSPLEX)

Article features

- Port density : 24

ETIM 10 features

- Suitable for number of couplings/adaptors : 24
- With number of couplings/adaptors : 24
- With front plate : Yes
- With housing : Yes
- With pigtailed : No
- Fibre type : Singlemode and Multimode 50/125
- Type of connector external : SC
- Type of connector interior : SC
- RAL-number : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Number of height units : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 224 mm