



19" CABLING FLOOR STANDING CABINET INIRACK GGM IR42810N



42 U
800 X 1000 mm
Black

A product optimised to meet to the essential.

Type :	Cabling
Frame :	Steel, mechanically screwed
Mounting profiles :	Two 19" mounting profiles adjustable in depth (zinc plated), "U" markings, 9.5 x 9.5 mm perforations
Front door :	Reversible securit glass door with side profiles, can be opened up to 190°, locked by using swing handle with key lock (N°333)
Rear panel :	Removable, locked by using 2 latches and key lock
Side panels :	Removable, locked by using 2 latches and key lock
Roof :	With Ventilation holes and rear pre-cut for cable entry (800 mm width cabinets are also equipped with the sides pre-cut for cable entry)
Base :	Full, with rear pre-cut for cables entry (800 mm width cabinets are also equipped with sides pre-cuts for cable entry)
Ground contact :	Adjustable feet (over 4 cm)
RAL :	9005 (Black)
Protection :	IP 20
Load capacity :	500 kg
Earthing kit included :	No
Capacity :	42 U
Depth (mm) :	1000
Height :	2020 mm
Width :	800 mm

RÉFÉRENCE	DESCRIPTION
GGM IR42810N	19" Cabling floor standing cabinet INIRACK 42U 800 X 1000 mm - Black