



Cable 4FO G657A2 9/125 μ m small bending radius micromodule construction, gel-free, aerial/duct, LSZH Dca white tube/HDPE black colour, dual sheathed GGM F4ASEMG6PST



Fibre optic cable, dedicated to indoor/outdoor use, pole mounted or underground. The double HDPE/LSZH sheath makes it possible to do away with the use of an indoor transition box thanks to the stripping of the outer HDPE sheath on penetration inside the house. Perfectly adapted for use in trunking or aerial, thanks to the FRP reinforcement embedded in the PE sheath.

Product features

- Convenient for aerial use : Up to 40 m under normal conditions
- AVCP System : AVCP4
- Packaging : 2 to 6 km reel, depending on FO densities
- Euroclass short : FCA
- Fiber color code : France Telecom
- Inner sheath : LSZH
- Operating temperature : From -40°C to $+70^{\circ}\text{C}$
- Other count of fibers : On demand
- Jacket : LSZH on demand
- Fiber type : Singlemode G657A2

Article features

- Modularity : 6 fibers per module
- Fiber amount : 4
- Strength member : FRP & waterblocking glass yarns wires

ETIM 10 features

- Number of fibres : 4
- Type of tube : Central tube
- Number of fibres per tube : 4
- Fibre type : Single mode 9/125
- Category : Other
- With strain relief : No
- With rodent protection : No
- Armouring/reinforcement : Other
- Material armouring : Other
- Material outer sheath : Other
- Specification material outer sheath : Polyethylene (PE)
- Colour outer sheath : Black
- Longitudinal water blocking cable : Yes
- Radial water blocking cable : Yes



- Cable metal free : Yes
- Cable geometry : Round
- Flame retardant according to IEC 60332-3-21 (Cat A F/R) : No
- Low smoke according to EN IEC 61034-2 : Yes
- Halogen free according to EN IEC 60754-1 : No
- Halogen free according to EN IEC 60754-2 : No
- Halogen free according to EN IEC 60754-3 : No
- Reaction-to-fire according to EN 13501-6: Class : Dca
- Reaction-to-fire according to EN 13501-6: Smoke production : s2
- Reaction-to-fire according to EN 13501-6: Flaming droplets/particles : d0
- Reaction-to-fire according to EN 13501-6: Acidity : a1
- Oil resistant according to EN IEC 60811-404 : No
- Resistant to chemicals : No
- Outer diameter approximate : 6 mm
- Max. tensile strength during installation : 8 kN
- Suitable for underground installation : No
- Blow in : Yes
- Weight : 30 kg/km