



Bullet bi-spectrum thermal camera. Resolution 4MP Fire detection, Smart intrusion prevention IP67 Light Hunter Technology Thermal sensor resolution 256*192

UNW TIC2A32SAF34F4ACI1



The TIC2A32SA-F3-4F4AC-I1 Bullet camera redefines surveillance with its advanced Thermal & Optical Bi-spectrum technology, providing dual video outputs for both thermal and optical images over a single IP address. This feature ensures versatile application in various environments. The camera also features a high-sensitivity 1/2.8" CMOS sensor for exceptional low-light performance and a thermal module that supports accurate fire and smoke detection. With smart intrusion prevention, advanced temperature measurement, and IP67/IK10 ratings for durability, this camera is optimized for demanding security needs. Additionally, Ultra H.265 compression and up to 512GB edge storage ensure high efficiency and convenience.

ETIM 10 features

- Model : Standard (Fixed)
- Construction type : Bullet shape
- Thermal camera : Yes
- Number of pixels (Megapixel) : 4
- With lens : Yes
- Modular (lens and camera separated) : No
- Focal size : 4 - 4
- Shutter control : DC
- Motor zoom : No
- Suitable for wall mounting : Yes
- Suitable for ceiling mounting : Yes
- Suitable for surface mounting : Yes
- Flush-mounted installation/built-in installation : No
- Suitable for outdoor use : Yes
- Communication medium wired : Yes
- Type of transmission medium : Twisted Pair
- Type of interface : None
- Protocol : TCP/IP
- Power over Ethernet (PoE) : 802.3 af (PoE)
- Picture system : PAL
- Property picture system : Colour
- With infrared lighting : Yes
- Max. infrared reach : 40 m
- With white light : No
- With video motion detector : Yes
- Memory capacity : 256 Go
- Number of digital inputs : 2
- Number of digital outputs : 2
- Number of audio inputs : 1
- Number of audio outputs : 1
- HDMI-connection : No
- Mini HDMI-connection : No
- VGA-connection (D-Sub 15-pole) : No
- DVI-connection : No



- BNC-connection : No
- DisplayPort-connection : No
- Mini DisplayPort : No
- S-Video-connection : No
- USB-C-connection : No
- Impact strength : None
- Degree of protection (IP) : IP67
- Horizontal field of view : 72,9 - 72,9
- Vertical field of view : 44,4 - 44,4
- Power consumption : 12 W
- Supply voltage : 12 - 12
- Voltage type : DC
- Colour : White
- Height : 83 mm
- Width : 95.7 mm
- Depth : 269.1 mm
- Compatible with Apple HomeKit : No
- Compatible with Google Assistant : No
- Compatible with Amazon Alexa : No
- IFTTT support available : No