



Preloaded 1U black patchpanel with 12 LC duplex OM3 adapters with ceramic ferule + 24 semi-tight buffer easy-strip colored pigtails + splice trays, spooling accessories, PG13,5 Cable gland

GGM TIREQ12LC3



Sliding optical patch panel equipped with 12 LC duplex multimode adapters + 24 LC OM3 pigtails.

Product features

- Cable entries : 2x20mm + 4x10mm
- Depth (mm) : 200
- Height (mm) : 44
- Number of ports : 24 port
- Pigtails : Colored, 1.5 m long
- Quick installation : Opening up to 45° for easy handling
- Weight (kg) : 2.6
- Width (mm) : 483

Article features

- Accessories included : 1 cable gland (PG 13.5), 1 splice management kit for 24 fusion splices, 8 bunny clips

ETIM 10 features

- Suitable for number of couplings/adapters : 24
- With number of couplings/adapters : 12
- With front plate : Yes
- With housing : Yes
- With pigtails : Yes
- Fibre type : Multi mode 50/125
- Fibre class : OM3
- APC-version : No
- Type of connector external : LC-Duplex
- Type of connector interior : LC-Duplex
- Colour : Black
- RAL-number : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Number of height units : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 200 mm