



**Preloaded 1U black patchpanel with 24 ST simplex OM2/OM3 metal adapters
with ceramic ferule + spooling accessories, splice management support,
PG13,5 Cable gland
GGM TIRRA24ST50**



Sliding patch panel equipped with 24 ST multimode connectors.

Product features

- Cable entries : 2x20mm + 4x10mm
- Depth (mm) : 200
- Height (mm) : 44
- Number of ports : 24
- Port identification : Numbering and marking space available on the front
- Quick installation : Opening up to 45° for easy handling
- Supplied accessories : Splice tray, 2 cable glands (PG 13.5), bunny clips

Article features

- Accessories included : 1 cable gland (PG 13.5), 1 splice management kit for 24 fusion splices, 8 bunny clips
- Width (mm) : 483
- Weight (kg) : 2.6

ETIM 10 features

- Suitable for number of couplings/adaptors : 24
- With number of couplings/adaptors : 24
- With front plate : Yes
- With housing : Yes
- With pigtails : No
- Fibre type : Multi mode 50/125
- Fibre class : OM3
- APC-version : No
- Type of connector external : ST
- Type of connector interior : ST
- Colour : Black
- RAL-number : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Number of height units : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 200 mm