



**INITIO preloaded 1U black patchpanel with 12 LC duplex singlemode adapters
+ splice tray**
GGM TO12LCDSM



Designed to meet essential requirements, the INITIO pre-equipped fibre patch panels offer excellent quality/price ratio

Product features

- Number of ports : 24 port
- Port identification : Numbering and marking space available on the front
- Number of cable entries : 6 x cable entries at the rear (2x 24 mm ; 2x 22 mm ; 2x 20 mm)
- Quick installation : Opening up to 45° for easy handling
- Fixing brackets : Adjustable depth
- Width (mm) : 483
- Depth (mm) : 224
- Height (mm) : 44
- Weight (kg) : 2.7
- Colour : Black
- Supplied accessories : Splice tray, 2 cable glands (PG 13.5), bunny clips

Article features

- Accessories included : Splicing cassette, spooling rings, blankers, 2 PG 13.5 cable glands, screws
- Cable entries : 6 rear cable entries (2x 24 mm ; 2x 22 mm ; 2x 20 mm)
- Pigtails : N/A

ETIM 10 features

- Suitable for number of couplings/adaptors : 12
- With number of couplings/adaptors : 12
- With front plate : Yes
- With housing : No
- With pigtails : No
- Fibre type : Single mode
- Fibre class : OS2
- APC-version : No
- Type of connector external : LC-Duplex
- Type of connector interior : LC-Duplex
- RAL-number : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Number of height units : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 206 mm