



RJ45 Crossover Patchcord Category 5e 1Gbit/s, PVC cable, outer shielded F/UTP, copper wires AWG26/7, 50µ gold plated, snagless connectors, OD : 5,4mm, light grey RAL7035, 0m50

GGM CAT5EBX05M



Warning !
This picture does not show the exact color

Crossover paired patch cord used to connect certain equipment in the Ethernet environment (generally equipment of the same type in 10BaseT and 100BaseT. PC to PC, Hub to Hub, ...).

- Applications : IEEE802.3 : 1000Base-T, 100Base-Tx, 10Base-T
- Shielding : F/UTP
- Category : 5E
- Standards : EIA/TIA 568-A-5
- Outersheath diameter : 5,6
- Frequency range : From 0 to 100 Mhz
- Impedance : 100
- Gauge (awg) : 26
- Boot : Molded slim boots
- Conductor type : Copper
- NVP (%) : 67
- Cable schematics : Cross
- Fire behaviour : IEC 60332-3
- Connector type : RJ45
- Sheath type : PVC
- Outer jacket colour : Grey
- Packaging : By piece
- Shield type : F/UTP
- Length : 5 m
- Connector A : RJ45 8(8)
- Connector B : RJ45 8(8)
- Jacket colour : Grey
- Snagless : Yes
- Boot colour : Red
- Fire retardant : No
- Oil resistant : No
- Number of pairs : 1x4
- AWG : 26
- Wire scheme : Crossed
- NVP : 67 %