



IP68LC/UPC - LC/UPC singlemode OS2 2 meters duplex patchcord, yellow colour, 3mm jacket
GGM IP68S2LC2M



Dedicated to severe use in industrial environments in particular, the GIGAMEDIA IP68 jumpers offer significant protection against dust, mould and other liquid splashes.
Available from stock in LC duplex, OM3 or OS2 single-mode versions.

Product features

- Protection (IP) : IP68
- Connector : LC
- Reinforcement : Aramid yarns
- Locking mechanism : Bayonet
- Housing : IEC 61076-3-106, variant 01, style 2
- Outersheath diameter : 35mm
- Max. Tensile : 200N
- Mating cycles : 500 (variation 0,3dB)
- Operating temperature : -20°C to +75°C
- Other lengths/modes : On demand

Article features

- Fiber type : Singlemode OS2
- Polishing type : UPC
- Length (m) : 2
- Outer jacket colour : Yellow
- Typical insertion loss (dB) : <= 0,30
- Return loss (dB) : >= 50
- Weight (kg) : 0.05

ETIM 10 features

- Fibre type : Single mode
- Category : OS2
- Number of fibres : 2
- Cable type : Duplex
- Length : 2 m
- Type of connector connection 1 : LC-Duplex
- Type of connector connection 2 : LC-Duplex
- Case connector connection 1 : IEC 61076-3-106 variant 1
- Material connector housing, connection 1 : Plastic
- Case connector connection 2 : None
- APC-version : No
- Colour outer sheath : Yellow



- Anti-kink sleeve : Put-on
- Oil resistant according to EN IEC 60811-404 : No
- Suitable for cable guide chain : No
- Degree of protection (IP) : IP68