Cable 4 fibers OM4 50/125 µm multimode central loose tube gel-free Cable, indoor/outdoor use with hydro-blocking glass yarns anti-rodent protection, LSZH B2ca outer jacket, erika violet colour

GGM FO4B4FRBLST



Loose structure indoor/outdoor cable (250 µm fibres) steel armoured, LSOH.
sheath Equipped with a steel reinforcement, it is resistant to crushing and can be buried directly.
Available with an LSOH-FR B2ca outer sheath, it is suitable for the most demanding environments in terms of fire performance.

Product features

- Cable type : Loose tube 250 µm
- Installation : indoor/outdoor
- Watertightness : Dry & longitudinal
- Fiber color code : IEC 60304
- Jacket : LSOH
- Euroclass : B2ca

Article features

- Bandwidth @1300 nm : OM4 >= 500 MHz/km
- Bandwidth at 1310/1550 nm : N/A
- Bandwidth @850 nm : OM4 >= 4700 MHz/km
- Bandwidth at 850 nm emb : OM4 >= 4700 MHz/km
- Bending radius - minimum static (mm) : 92
- Bending radius - minimum dynamic (mm) : 122
- Cable weight (kg/km) : 45
- Packaging : On cut
- Crush resistance (N) : 2000
- Diameter (mm) : 6.1
- Fire behaviour : EN 13501-6 : B2ca, s1a, d1, a1 ; EN 50575, EN 50399, EN 60332-1-2
- Marking : [Length] [GIGAMEDIA 4FO 50/125 OM4 CLT LSZH] [B2ca s1a d0 a1] [CLT FO CABLE FCTB004U] [Week/Year]
- Attenuation : At 850 nm: om4 <= 2.0 db/km
- Fiber amount : 4
- Strength member: : Reinforced glass yarns protection against rodents
- Operating temperature : From -20°C to +60°C
- Bandwidth at 850 nm dmd : OM4 >= 3500 MHz/km
- Central strength member : No
- Jacket type : LSZH-FR
- Tensile strength (n) : 1200
- Operating environment : Indoor / Outdoor

ETIM 10 features



- Number of fibres : 4
- Type of tube : Central tube
- Number of fibres per tube : 4
- Fibre type : Multi mode 50/125
- Category : OM4
- With strain relief : No
- With rodent protection : Yes
- Armouring/reinforcement : Other
- Material armouring : Other
- Material outer sheath : Other
- Specification material outer sheath : Other
- Colour outer sheath : Purple
- Longitudinal water blocking cable : Yes
- Radial water blocking cable : Yes
- Cable metal free : Yes
- Cable geometry : Round
- Flame retardant according to IEC 60332-1-2 : Yes
- Flame retardant according to IEC 60332-3-21 (Cat A F/R) : Yes
- Low smoke according to EN IEC 61034-2 : Yes
- Halogen free according to EN IEC 60754-1 : Yes
- Halogen free according to EN IEC 60754-2 : Yes
- Reaction-to-fire according to EN 13501-6: Class : B2ca
- Reaction-to-fire according to EN 13501-6: Smoke production : s1a
- Reaction-to-fire according to EN 13501-6: Flaming droplets/particles : d0
- Reaction-to-fire according to EN 13501-6: Acidity : a1
- Oil resistant according to EN IEC 60811-404 : No
- Resistant to chemicals : No
- Outer diameter approximate : 6.1 mm
- Min. permitted bending radius, stationary application/permanent installation : 91.5 mm
- Max. tensile strength during installation : 12 kN
- Suitable for underground installation : No
- Blow in : No
- Weight : 45 kg/km