IP54 FTTx empty ABS plastic box, up to 60 fibers (fusion splices) or to be loaded with 6 LC duplex adapters, in multimode or in singlemode, suitable for wall or pole fixation, light grey colour (RAL7035)

GGM IP54FTTXBOX



This IP54 enclosure has been specially designed for easy connection of optical fibers, via fusion splicing (60 optical fibers) or pre-terminated drop cables (up to 12 optical fibers - 6 duplex LC connections).

It can therefore be used for FTTH or FTTA (5G antennas) deployments.

Pole or wall mounting.

Product features

- Produit : IP54 box

Article features

- Material : ABS plastic
- Fiber count : 60
- Max. amount of splice trays : 5
- IP Protection : IP54
- Impact protection : IK08
- Locking mechanism : With clips
- Adapter : LC duplex
- Fiber type : Singlemode OS2/G652D or G657
- Cables Inputs/Outputs : 4x 1.6-14 mm ; 12x 1.6-10 mm
- Operating temperature (°C) : -35 °C to +65 °C
- Color : Grey
- Weight (kg) : 1
- Dimensions: (mm) : 297.5 x 239 x 73
- Option : 12-fibre splice cassette GGM 12CLIPTRAY
- Pole bracket : Included

ETIM 10 features

- Suitable for number of fibres : 60

- Type of coupler : Fusion splice
- Separated compartments : No
- Lockable : Yes
- Degree of protection (IP) : IP54