GIGAMEDIA
SMART BUILDING SOLUTIONS

Basic 1U metal panel space for 16 monobloc ports black

GGM PANV16PMKB



From a completely modular design or not, the GIGAMEDIA range of panels offers an economic solution and competitive cost/port ratio. It has possibility for markings and identification. Ready to accept a substantial number of active links, they are robust, have a rear support plate and thus guarantee reliability when mounted in a 19" environment. NB: Delivered without connectors

- Applications : N/A
- Category : N/A
- Color code : N/A
- Standards : ANSI/TIA-568.2-D, ; EN 50173 ; ISO/IEC 11801
- Connector type : Female
- Height in U : 1
- Impedance : 100
- Connection mode : N/A
- Equip : No
- Port density : 16
- Port identification : Numbering, marking area
- Color : Black
- Pro. 110 IDC block with cutting blade : N/A
- Number of connections : 16
- Shielded : Yes
- Connection type : Other
- Height (U) : 1
- Colour : Black
- RAL : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Height : 44.45 mm
- Width : 482.6 mm
- Depth : 160 mm
- Compatible with Grade2TV according to XP-C 90-483 : No
- Compatible with Grade3TV according to XP-C 90-483 : No