Preloaded 1U black patchpanel with 6 LC duplex OM4 adapters with ceramic ferule + 12 semi-tight buffer easy-strip colored pigtails + splice tray, spooling accessories, PG13,5 Cable gland

GGM TIREQ6LCOM4



Sliding patch panel equipped with 6 LC duplex connectors + 12 LC OM4 pigtails

Product features

- Height (mm) : 44
- Number of ports : 12 port
- Pigtails : Colored, 1.5 m long
- Quick installation : Opening up to 45° for easy handling
- Supplied accessories : Splice tray, 2 cable glands (PG 13.5), bunny clips

Article features

- Cable entries : 2 x 20 mm + 4 x 10 mm
- Depth (mm) : 200
- Width (mm) : 483
- Weight (kg) : 2.6

ETIM 10 features

- Suitable for number of couplings/adaptors : 24
- With number of couplings/adaptors : 6
- With front plate : Yes
- With housing : Yes
- With pigtails : Yes
- Fibre type : Multi mode 50/125
- Fibre class : OM4
- APC-version : No
- Type of connector external : LC-Duplex
- Type of connector interior : LC-Duplex
- Colour : Black
- RAL-number : 9005
- Mounting method : 482.6 mm (19 inch) mounting
- Number of height units : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 200 mm