# Preloaded 1U black patchpanel with 6 LC duplex OM3 aqua adapters with ceramic ferule + spooling accessories, splice management support, PG13,5 Cable gland

**GGM TIRRA6LCOM3**



Designed to facilitate the handling, installation and maintenance of optical fibers, GGM TIRRA6LCOM3 optical drawers are equipped with 6 turquoise OM3 multimode duplex LC fittings, and can manage up to 48 fibers.

## Product features

- Cable entries : 2x20mm + 4x10mm
- Depth (mm) : 200
- Height (mm) : 44
- Number of ports : 24 port
- Pigtails : Colored, 1.5 m long
- Quick installation : Opening up to 45° for easy handling
- Weight (kg) : 2.6
- Width (mm) : 483

## Article features

- Accessories included : 1 cable gland (PG 13.5), 1 splice management kit for 24 fusion splices, 8 bunny clips

## ETIM 10 features

- Suitable for number of couplings/adaptors : 24
- With number of couplings/adaptors : 6
- With front plate : Yes
- With housing : Yes
- With pigtails : No
- Fibre type : Multi mode 50/125
- Fibre class : OM3
- APC-version : No
- Type of connector external : LC-Duplex
- Type of connector interior : LC-Duplex
- Colour : Black
- RAL-number : 9005
- Mounting method : 482.6 mm (19 inch) mounting



- Number of height units : 1
- Height : 44 mm
- Width : 483 mm
- Depth : 200 mm